



# **Care, Warranty, & Installation Guidelines**

**T**hank you for choosing an NBI product. Our continued commitment lies in the complete satisfaction of each and every product we sell. If for any reason you are not satisfied with the product you have received, you may return it within 30 days for a full refund.

Our success lies in our prompt, professional, and personal attention we strive to give. Should you have any suggestions that you feel we could improve on, please feel free to contact us.

Sincerely,

The Staff @ NBI Drainboard Sinks

# **CARE AND CLEANING GUIDE**

***For best results, always keep the following in mind when caring for your new acrylic sink:***

- Always test your cleaning solution on an inconspicuous area before applying to the entire surface.
- Never use abrasive cleaners. Use of such will dull the sinks finish over time.
- Use a soft, dampened sponge or cloth to clean the surface. Never use an abrasive material such as a brush or scouring pad.
- Do not allow cleaners to soak for unnecessary or extended periods. Wipe surfaces clean and rinse completely with water to remove cleaning products.
- Never allow drain cleaners or harsh chemicals to contact the sinks surface.
- Always wait until pots and contents have cooled before placing on or into the sink.
- Never pour hot grease onto the sinks surface.
- If knives or sharp objects are to be used in the sink always use a cutting board or sink protector.
- If minor scratches develop over time, they can be buffed and polished using an appropriate crème polish.

# **FIVE YEAR LIMITED WARRANTY**

This warranty is effective for all NBI (Nelsons Bathtub Inc.) acrylic sinks. Warranty begins on date of purchase (regardless of installation date).

This warranty excludes:

1. Any obligation other than replacement or repair of defective parts
2. Any labor charges, removal or reinstallation expense, freight or any incidental or consequential damages resulting from any defective product.
3. Normal wear and tear, including chips and/or scratches.

This warranty shall be voided by any of the following:


1. Modification.
2. Improper installation, care or maintenance of the product.
3. Use of the product for any purpose or in any manner other than for which it is specifically intended.
4. Improper maintenance contrary to the care instructions.

This warranty supersedes any and all other warranties, expressed or implied. The foregoing warranties are exclusive and made only to the buyer. No other warranty, whether expressed, implied or statutory, including any warranty of merchantability or fitness for particular purpose shall exist in connection with any of the warranties on behalf of Nelsons Bathtub Inc. in addition to or different from those herein given, or to assume for Nelsons Bathtub Inc. any other liability in connection with any of its product except in a written statement which is signed by an officer of Nelsons Bathtub Inc. expressly and intentionally giving such warranties or expressing such liabilities. Nelsons Bathtub Inc. is NOT liable for incidental or consequential damage, loss of time, inconvenience, incidental expenses, labor or material charges or any other costs related to the application of this warranty.


# NBI INSTALLATION GUIDELINES

*Please read all instructions carefully before beginning installation!*


**PLEASE NOTE:** Most NBI sinks are designed so that the drainboard sections do not interfere, make contact, or require a countertop cutout to be made below the drainboard sections of the sink. Generally, the only cutout required to facilitate a proper installation would be to accommodate the sinks basin or basins. The following instructions will remove the area of countertop below the drainboards. If you prefer not to make the additional cutouts below the drainboards you may locate and position cutout lines for the sinks basin or basins only.




**STEP 1:** Measure the sinks overall dimensions (length and width) and make note of these measurements.



**STEP 2:** Using tape lines or crayon, transfer the dimensions you noted in Step 1 onto the countertops surface, positioning and aligning them in the desired location of the installed sink. These markings should now represent the sinks outer perimeter edges. **Cautionary Note: Make sure to radius all corner markings as necessary and verify your dimensions and markings!**




**STEP 3:** Measure in 1 ¼" and draw new lines that run parallel to the sink's dimensional lines that were made in Step 2.



**STEP 4: Cautionary Note: Verify all dimensional lines before proceeding!** Following the inner line that was drawn in Step 3 carefully cut out the countertop surface.

**STEP 5:** Temporarily position the sink in the countertop opening to ensure a proper fit. Make small adjustments to the cutout if necessary, making sure never to cut beyond the outer lines that were drawn in Step 2.

**STEP 6:** Carefully remove the sink and clean the countertop surface removing any tape that may have been used.



**STEP 7:** Place the sink back into the countertop opening and position it in its final location. Apply a continuous bead of the appropriate colored (we recommend the sink's finish color be used) kitchen & bath adhesive sealant around the entire perimeter of sink's flange where it meets the countertop surface. Remove and cleanup excess sealant and allow curing time per the sealant manufacturer's recommendation.

**STEP 8:** Make all remaining plumbing connections per local code and/or to the manufacturer's recommendations.

# FOR EASY FUTURE REFERENCE, FILL OUT AND RETAIN FOR YOUR RECORDS:

Date Purchased: \_\_\_\_\_

Product Model Number: \_\_\_\_\_

Order Number: \_\_\_\_\_

## **NBI Drainboard Sinks**

13105 Rachael Blvd

Alachua Florida 32615

Tel: 352-213-3119

Website URL: [www.nbidbs.com](http://www.nbidbs.com)

Email: [info@nbidrainboardsinks.com](mailto:info@nbidrainboardsinks.com)